

DIGI® S-T-U-V



STANDARD FEATURES

- IP66-rated
- Platform support in each corner
- Shock resistant load cells
- Rated to 300% overload

APPROVALS



Measurement
Canada
Approved

SPECIFICATIONS

Recommended Exc. Voltage:

5-12VDC

Max Exc. Voltage:

20 VAC/DC

Output Impedance:

350 ±10Ω

Insulation Resistance:

500 MΩ or more

Rated Output:

0.83 mV/V ±7.5%

Rated Input:

1 mV/V ±7.5%

Load Cell Cable Length:

S-S/S-T: 9 ft (3 m) with 14 pin connector

S-U: 18 ft (5.5 m) with 14 pin connector

S-V: 28 ft (8.5 m) with 14 pin connector

Temperature Range:

14°F to 104°F (-10°C to 40°C)

Warranty:

Two-year limited warranty

Approvals:

NTEP CC 02-111, Class III, 5000d

Measurement Canada AM-5393, Class III 5,000d

PART NUMBER/PRICE

PART#	MODEL	CAPACITY	DIMENSIONS	EST. SHIP WEIGHT	PRICE
Carbon Steel Platform – Stainless Steel Platter					
73248†	S-SL	60 lb (30 kg)	13 x 17 x 3.5 in	30 lb (14 kg)	Consult
73246	S-SL	150 lb (60 kg)	13 x 17 x 3.5 in	30 lb (14 kg)	Consult
73247	S-SL	300 lb (150 kg)	13 x 17 x 3.5 in	30 lb (14 kg)	Consult
73250	S-TL	150 lb (60 kg)	17 x 21 x 4.5 in	50 lb (23 kg)	Consult
73251	S-TL	300 lb (150 kg)	17 x 21 x 4.5 in	50 lb (23 kg)	Consult
73252†	S-TL	500 lb (300 kg)	17 x 21 x 4.5 in	50 lb (23 kg)	Consult
74508	S-UL	150 lb (60 kg)	24 x 28 x 5 in	90 lb (41 kg)	Consult
73256	S-UL	300 lb (150 kg)	24 x 28 x 5 in	90 lb (41 kg)	Consult
73257	S-UL	500 lb (300 kg)	24 x 28 x 5 in	90 lb (41 kg)	Consult
76511*	S-VL	1,500 lb (600 kg)	24 x 28 x 6 in	130 lb (59 kg)	Consult

* Non NTEP

† Measurement Canada Approved